



# SIROMER Equipment

Your Tractor's Best Friend

## HAY RAKE



Ideal for rowing up before baling fully will also spread freshly mown grass to aid with fast drying

As a tedder:

- 1). Spread, swath or windrow so crops dry down faster,
- 2). Tailor your tedding operations to a variety of crops and conditions by varying PTO speed or tine position,
- 3). Fixed-tine position provides aggressive tedding and is ideal for use in fresh-cut material or crops where leaf and shatter losses are not a concern
- 4). Cam-operated tine position allows the tine bar rollers to follow the cam track to lift and release crop gently and save valuable leaves

As a rake:

- 1). Precise raking action produces fluffy, uniform windrows that dry evenly
- 2). Self-centring wheels provide extra manoeuvrability by allowing you to make sharp turns and back up easily without lifting the machine.

Strong, rugged frame provides years of dependable performance.

Three wheel-height position let you adjust for different crops, conditions and operations.

Vertical tines pick up fewer stones and less debris than horizontal tines for cleaner tedding and raking.

Convenient jack simplifies three-point hitch arrangements.

For use in conjunction with the Siromer P10 baler

Tedding width	Weight	Tines per rotor	Numbers of rotors	Working speed	Power required
250cm	160kg	4	6	4-8km/h	20-40hp

**Tel: 01253 799 029**

**Web: [www.siromer.online](http://www.siromer.online)**

Specification subject to change without notice.  
Information is for guidance only.