



SIROMER Equipment

Your Tractor's Best Friend

SIROMER FLAIL MOWER



as fixed semi offset or with hydraulic offset. A double acting spool is required for operation of hydraulic offset. The arrangement of hinged, heavy-duty, hammer blades revolving horizontally on pivots with rear roller to maintain height above the ground, allows the flail mower to be used on both a smooth lawn and uneven grass. The cutting height is controlled by adjustable skids and rear roller. The opening back has 4 settings allowing the fineness of the cut to be changed whilst preventing grass clogging.

FEATURES:

- Opening back.
- Adjustable skids and rear roller.
- PTO shaft included.

Model	Size	Working Width	Weight	HP	Hammers	Offset
M82	1.05m	1020mm	250kg	16-25	16	Semi
M84	1.25m	1220mm	277kg	20-30	20	Semi
M85	1.45m	1420mm	288kg	30-40	24	Semi
M86	1.55m	1520mm	299kg	35-50	24	Semi
M87	1.65m	1620mm	306kg	35-50	28	Semi
M88	2.00m	1960mm	430kg	40-75	32	Semi
M95	1.45m	1420mm	342kg	30-40	24	Hydraulic
M96	1.65m	1620mm	367kg	35-50	28	Hydraulic
M97	1.75m	1720mm	386kg	40-75	28	Hydraulic
M99	2.20m	2170mm	470kg	50-90	34	Hydraulic

Tel: 01253 799 029

Web: www.siromer.online

Specification subject to change without notice.
Information is for guidance only.